

MATERIAL SAFETY DATA SHEET
SECTION I - XVI

PRODUCT CODE: BB105GP
DATE PRINTED: 04/28/06

SECTION I - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCTION DESCRIPTION: BB-105 GRAY PRIMER

MSDS EFFECTIVE ISSUE DATE: 04/23/06

COMPANY NAME: WOHL COATINGS CO. ,
6161 MAPLE AVE.

ST. LOUIS, MO 63130 ,

DAY PHONE NUMBER: 314-725-3400

EMERGENCY PHONE NUMBER: (800)-535-5053

SECTION II - COMPOSITION/INFORMATION ON INGREDIENTS

NON-HAZARDOUS MATERIAL ' CAS No.: NA Percent By Weight: 15 To 20
OSHA PEL: ppm mg/M3 TWA ACGIH TLV: ppm mg/M3 TWA
LD50: LC50: V.P(A) LEL: UEL:
Listed On(B) 1: N 2: N 3: N 4: Y 5: N 6: N 7: N 8: N

VM&P NAPHTHA ' * CAS No.: 64742-89-8 Percent By Weight: 15 To 20
OSHA PEL: 300 ppm 1350 mg/M3 TWA ACGIH TLV: 300 ppm 1370 mg/M3 TWA
LD50: LC50: V.P(A) 4.1 @68 LEL: 0.9 UEL:
Listed On(B) 1: N 2: N 3: N 4: Y 5: N 6: N 7: N 8: N

MAGNESIUM SILICATE ' * CAS No.: 14807-96-6 Percent By Weight: 15 To 20
OSHA PEL: NA ppm 2 mg/M3 TWA ACGIH TLV: NA ppm 2 mg/M3 TWA
LD50: LC50: V.P(A) NA LEL: NA UEL:
Listed On(B) 1: N 2: N 3: N 4: Y 5: N 6: N 7: N 8: N
Respirable dust for TLV and PEL.

CALCIUM CARBONATE ' * CAS No.: 1317-65-3 Percent By Weight: 10 To 15
OSHA PEL: NA ppm 15 mg/M3 TWA ACGIH TLV: NA ppm 10 mg/M3 TWA
LD50: LC50: V.P(A) NA LEL: NA UEL:
Listed On(B) 1: N 2: N 3: N 4: Y 5: N 6: N 7: N 8: N

NAPHTHA ' * CAS No.: 8030-30-6 Percent By Weight: 10 To 15
OSHA PEL: 500 ppm mg/M3 TWA ACGIH TLV: 100 ppm mg/M3 TWA
LD50: NE LC50: NE V.P(A) LEL: NA UEL: NA
Listed On(B) 1: N 2: N 3: N 4: Y 5: N 6: N 7: N 8: N

HEPTANE ' * CAS No.: 142-82-5 Percent By Weight: 5 To 10
OSHA PEL: 400 ppm NE mg/M3 TWA ACGIH TLV: 400 ppm NE mg/M3 TWA
LD50: NE LC50: NE V.P(A) LEL: 1.0 UEL: 7.1
Listed On(B) 1: N 2: N 3: N 4: Y 5: N 6: N 7: N 8: N

TITANIUM DIOXIDE ' * CAS No.: 13463-67-7 Percent By Weight: 5 To 10
OSHA PEL: NA ppm 10 mg/M3 TWA ACGIH TLV: NA ppm 10 mg/M3 TWA
LD50: LC50: V.P(A) NA LEL: NA UEL:
Listed On(B) 1: N 2: N 3: N 4: Y 5: N 6: N 7: N 8: N

TOLUENE ' * CAS No.: 108-88-3 Percent By Weight: 5 To 10
OSHA PEL: 100 ppm 375 mg/M3 TWA ACGIH TLV: 50 ppm 188 mg/M3 TWA
LD50: LC50: V.P(A) 22 @68 LEL: 1.0 UEL:
Listed On(B) 1: N 2: Y 3: Y 4: Y 5: N 6: N 7: Y 8: N
Skin For TLV.

ORGANOPHILIC CLAY ' * CAS No.: 68953-58-2 Percent By Weight: 1 To 5
OSHA PEL: NA ppm 15 mg/M3 TWA ACGIH TLV: NA ppm 10 mg/M3 TWA
LD50: LC50: V.P(A) NA LEL: .05 UEL:

MATERIAL SAFETY DATA SHEET
SECTION I -XVI

PRODUCT CODE: BB105GP
DATE PRINTED: 04/28/06

SECTION II - COMPOSITION/INFORMATION ON INGREDIENTS Con't.

Listed On(B) 1: N 2: N 3: N 4: Y 5: N 6: N 7: N 8: N
oz./cu. ft. for LEL.

CRYSTALLINE SILICA * CAS No.: 14808-60-7 Percent By Weight: < 1.0

OSHA PEL: NA ppm 0.098 mg/M3 TWA ACGIH TLV: NA ppm 0.05 mg/M3 TWA

LD50: NA LC50: NA V.P(A) NA LEL: NA UEL:

Listed On(B) 1: N 2: N 3: N 4: Y 5: Y 6: Y 7: Y 8: N

RESPIRABLE DUST CAN CAUSE SILICOSIS, CANCER, AUTOIMMUNE DISEASES

DEFINITION OF SPECIAL MARKS AND LIST INFORMATION

* Defined as hazardous per 29 CFR 1910.1200

(1) Vapor Pressure In mm Hg

(B) LIST DEFINITION 1 = SARA 302/304 2 = SARA 313 3 = CERCLA 103(a) 4 = TSCA 5 = NTP Carcinogen

6 = IARC Carcinogen 7 = California Prop. 65 8 = OSHA Carcinogen

N = ITEM NOT ON THE LIST, Y = ITEM IS ON THE LIST

NOTE: Product will have hazards of all components when mixed for application.

SECTION III - HAZARDS IDENTIFICATION

EFFECTS OF OVEREXPOSURE - ACUTE:

Breathing: Irritation of the respiratory tract; may affect the brain or nervous system causing dizziness, headache, nausea, weakness and fatigue. Extreme exposure can result in unconsciousness and even respiratory arrest.

WARNING: Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Eye or Skin Contact: Causes eye and skin irritation.

Swallowing: Can cause stomach and/or intestinal irritation, nausea, vomiting and diarrhea. Aspiration of vomitus can cause chemical pneumonitis, which can be fatal.

CHRONIC: Crystalline silica has been classified as carcinogenic for humans (2A) by IARC. The excessive inhalation of crystalline silica is also a known cause of silicosis. (Risk depends on duration and level of exposure.) Other possible chronic effects are silicosis, cancer, scleroderma and tuberculosis. The main route of entry is inhalation of crystalline silica. Dry silica powder should be handled with great care. When the silica is mixed and wetted by the other components the risk of inhalation is greatly reduced.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: If you are allergic or have been sensitized to: epoxies, amines, isocyanates, detergents, or other chemicals see a physician prior to use. Use protective creams and resistant clothing to prevent contact with the product or the fumes.

(X)SKIN (X)BREATHING (X)SWALLOWING

SECTION IV - FIRST AID MEASURES

IF BREATHED: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, summon medical assistance immediately. If breathing ceases, restore using approved CPR techniques and summon medical assistance immediately.

IF EYE CONTACT: Flush with large amounts of water for at least 15 minutes. Get medical assistance.

IF ON SKIN: In case of skin contact, wash area thoroughly with soap and water. Remove soiled clothing. Get medical assistance if irritation persists.

IF SWALLOWED: DO NOT INDUCE VOMITING. Consult physician immediately. Aspiration of vomitus can cause chemical pneumonitis which can be fatal.

SECTION V - FIRE FIGHTING MEASURES

FLAMMABILITY CLASSIFICATION: FLASH POINT: 15 °F Setflash

OSHA 29 CFR - 1910.106(a)

Parts 18-19

Flammable Liquid - Class 1(B) Extremely Flammable (FHSA)

EXTINGUISHING MEDIA: In case of fire, use CO₂, Dry Chemical, Foam or other National Fire Protection Association (NFPA) approved method for treating a Class B Fire.

**MATERIAL SAFETY DATA SHEET
SECTION I - XVI****PRODUCT CODE: BB105GP
DATE PRINTED: 04/28/06**

SECTION V - FIRE FIGHTING MEASURES Con't.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Keep containers tightly closed. Isolate from heat and flame. Due to pressure build-up, closed containers exposed to extreme heat may explode. Never use a welding or cutting torch on or near container (even empty) as product or its residue may ignite. During emergency conditions, overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

SPECIAL FIRE FIGHTING PROCEDURES: Summon professional firefighters. Use full protective equipment including self-contained breathing apparatus. Water spray may be ineffective. If water is used, fog nozzles are preferable. If exposed to fire or extreme heat, water should be used to cool closed containers and prevent pressure build-up or possible auto-ignition.

SECTION VI - ACCIDENTAL RELEASE MEASURES

Remove all sources of ignition (flames, hot surfaces, and electrical, static or frictional sparks). Do not smoke. Avoid breathing vapors. Before attempting clean-up refer to hazard caution information in other sections of this material safety data form. Ventilate area. Contain spilled material and remove with inert absorbent and non-sparking tools. Store in closed containers until properly disposed of.

SECTION VII - HANDLING AND STORAGE

Keep away from heat, sparks and flame. Do not smoke. Extinguish all pilot lights and turn off all sources of ignition including heaters, fans and other non-explosion-proof electrical equipment, during use and until all vapors are gone. Vapors may ignite explosively or cause flash fire. Vapors may spread long distances and beyond closed doors. Prevent build-up of vapors by maintaining continuous flow of fresh air.

DANGER: Extremely flammable liquid and vapor.

Do not store above 120°F or near fire or open flame. Store large quantities in buildings designed to comply with OSHA 1910.106. Keep container closed when not in use. Do not transfer contents to bottles or other unlabelled containers. Do not reuse empty containers.

Keep out of reach of children. Product for use by professional painters and applicators only.

SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION

RESPIRATORY PROTECTION: All workers and bystanders must be protected from exposure above Section II limits. Avoid breathing vapors, spray mist or sanding dust. Application by brush, roller, squeegee, or trowel will result in the lowest release of hazardous materials. When spray applied in outdoor or open areas with unrestricted ventilation, and during sanding or grinding operations, use NIOSH/MSHA approved mechanical filter respirator to remove solid airborne particles of over spray or sanding dust. When used in restricted areas, wear NIOSH/MSHA approved chemical/mechanical filters designed to remove a combination of particulates and vapor. When used in confined areas, wear NIOSH/MSHA approved air supply respirators or hoods. Use NIOSH/MSHA approved respirators when flame cutting, welding, brazing and sanding material coated with this product. The fumes from these operations can be hazardous. Do not breathe them. Always use adequate ventilation.

Whenever using respirators refer to OSHA 1910.134 for proper respirator use and safety program. The applicator determines the type of area in which the application is being made (unrestricted, restricted, or confined). The best determination of respirator type to use in a particular application is to monitor for the hazardous materials during actual application. The applicator should contact a qualified safety engineer for proper selection of safety equipment based on the application conditions.

NIOSH has recommended that the permissible exposure limit for crystalline silica be changed to 50 micrograms respirable free silica per cubic meter of air (Time Weighted Average).

PROTECTIVE GLOVES: Do not get on skin. Solvent impermeable gloves to prevent contact are recommended.

EYE PROTECTION: Do not get in eyes. Solvent resistant safety eyewear with splash guards or sideshields is recommended to prevent contact.

OTHER PROTECTIVE EQUIPMENT: Do not get on skin. Solvent impermeable clothing and boots to prevent contact are recommended.

HYGIENIC PRACTICES: Remove and wash soiled clothing before reuse. Wash hands before eating, smoking or using the washroom. Remove any contaminated clothing and clean before reuse. Shoes and boots if contaminated must be replaced.

MATERIAL SAFETY DATA SHEET
SECTION I -XVIPRODUCT CODE: BB105GP
DATE PRINTED: 04/28/06

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

WATER SOLUBILITY: Negligible.

ODOR: Characteristic of solvents listed in SECTION II.

WEIGHT PER GALLON: 9.61 Pounds

PERCENT VOLATILE BY VOLUME: 57.68

EVAPORATION RATE:()Faster (X) Slower Than Ether

BOILING RANGE: NA

VAPOR DENSITY:(X)Heavier ()Lighter Than Air -

SECTION X - STABILITY AND REACTIVITY

STABILITY:()UNSTABLE (X)STABLE

INCOMPATIBILITY: Avoid contact with strong oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: May cause hazardous fumes when heated to decomposition or from mixed material that is kept in 1/2 gallon or larger mass longer than the potlife. The following represents a partial list: (from burning, heating, or reaction with other materials). Nitrogen oxide can react with water vapors to form corrosive nitric acid (TLV=2 ppm). Carbon Monoxide in a fire. Carbon Dioxide in a fire. Ammonia when heated. Nitrogen Oxides in a fire. Irritating and toxic fumes at elevated temperatures. Nitric acid in a fire, nitrosamines, unknown aldehydes. The oxides of nitrogen gases (except nitrous oxide) emitted on decomposition are highly toxic. An other unidentified phenolic and organic compounds and oxides of metals listed in Section II. Treat all of these fumes as hazardous and DO NOT BREATHE. DO NOT WELD THROUGH, HEAT OR BURN WITHOUT ADEQUATE PROTECTION OF ALL PERSONEL AND BYSTANDERS.

HAZARDOUS POLYMERIZATION:()MAY OCCUR (X)WILL NOT OCCUR.

MIXED PRODUCT SHOULD NOT BE KEPT IN QUANTITIES GREATER THAN 3 TO 6 LBS WEIGHT (approx. 1 QUART/1/2 GALLON VOLUME LONGER THAN 25 TO 35 MINUTES AT HIGH AMBIENT TEMPERATURES. The product reacts quickly when in large mixed masses and develops heat quickly. It is possible for the mass to reach decomposition temperatures and give off dangerous gasses. ALWAYS pour the material out in thin thickness (1/4 inch or less) to avoid the mass reaction.

SECTION XI - TOXICOLOGICAL INFORMATION

No information available.

SECTION XII - ECOLOGICAL INFORMATION

No information available.

SECTION XIII - DISPOSAL CONSIDERATIONS

Dispose of in accordance with local, state and federal regulations. Incinerate only in approved facility. Do not incinerate closed containers.

SECTION XIV - TRANSPORT INFORMATION

DOT CLASS: PAINT, 3, UN1263, PGII

SECTION XV - REGULATORY INFORMATION

This product or component contains 4.03 pounds per gallon (483 grams/liter) volatile organic compounds. The VOC less water and exempt solvents is 4.03 lbs./gal. (483 gms./L.)

This product contains a chemical known to the state of California to cause cancer, birth defects or other reproductive harm. This product contains a chemical known to the state of California to cause cancer.

SECTION XVI - OTHER INFORMATION

HMIS RATING: (H)ealth 1* (F)lammability 3 (R)eactivity 0

The information contained herein is based on data believed by WOHL COATINGS CO. to be accurate, but we do not assume any liability for the accuracy of this information. We neither suggest nor guarantee that any hazards mentioned are the only ones which exist. Anyone intending to rely on any recommendation or to use any equipment, technique or material mentioned should also satisfy himself that he can meet all applicable safety and health standards.